LED DECORATIVE HAMMERED ROOF

Traditional designed pierced shade and scalloped edge combines with the energy efficient benefit of LED technology. Coordinates with matching LED path light 15871 and 15843 on page 10.	
15763 TZT - Textured Tannery Bronze™ (Marine grade powder coat)	
Brass	
1 Integrated High Output Nichia® LED, tightly binned for color uniformity, and constant current driver	
3000K (-200/+125) / 80s CRI	1 16 AN
1.9 W, 2.4 VA Multiply fixture VA by the number of fixtures used to determine size of transformer	TZT AN AND
9V-15V AC/DC with no loss in output due to constant current technology	
Tested to an L-70 of 40,000 hours	3.375"
3000K = 50 Lm 3000K= 26 Lm/W	3"
72" of usable #18-2, SPT-1-W leads. Cable connector supplied	APSTRA
Stainless steel mounting bracket	2"
Subjected to Highly Accelerated Life Testing - 3rd party reliability testing Not for use with electronic transformers	E CO
Mounting Height 0' 0.5' 1' 2' 3' 4' 5'	Contraction of the second s
6° 69.4 14.4 1.8 0.08 0.03 - 12" 15.3 8.6 3.4 0.37 0.08 0.02 -	
WT763	POWERED BY
	Guaranteed not
	to burn out for 15 years (10 commercially)

Professional-grade LED lighting and system components, designed and engineered for optimum all-weather performance with natural lighting effects, deliver professional results.

Enhance The Night - www.landlight.ca

LandLig

Enhance The

۱t

Niaht