LED BRICK LIGHT

3 25

9.5

3.25

15774 Heat-resistant glass lens

15773

Louver face

15773

2.375

15774

2.375"

Guaranteed not to burn out for 15 years (10 commercially)

AZT

8

AZT

8"

Designed to be integrated into brick wall during construction. LED version is also usable in vertical risers. Casts a low, even spread of energy efficient LED light. Available with or without louvers.

15773 AZT - Textured Architectural Bronze with louver face (Marine grade powder coat) 15774 AZT - Textured Architectural Bronze with heat resistant glass lens (Marine grade powder coat)

Cast Aluminum

2 Integrated High Output Nichia $^{\odot}$ LEDs, tightly binned for color uniformity, and constant current driver

3000K (-200/+125) / 80s CRI

3.8 W, 4.8 VA Multiply fixture VA by the number of fixtures used to determine size of transformer

9V-15V AC/DC with no loss in output due to constant current technology

Tested to an L-70 of 40,000 hours

3000K = 100 Lm 3000K= 26 Lm/W

Wire connection must be made inside fixture

Stainless steel mounting hardware and junction box (included)

15073 - on page 113, 15074 - on page 113

Subjected to Highly Accelerated Life Testing - 3rd party reliability testing. Not for use with electronic transformers

Mounting Height	0'	0.5'	1'	1.5'	2'	2.5	3'	4'	
12"	0.22	2.08	1.87	1.85	1.3	0.85	-	-	
24"	0.12	0.16	0.29	0.72	0.77	0.68	0.52	-	
36"	0.04	0.05	0.09	0.12	0.16	.026	.026	_	





Professional-grade LED lighting and system components, designed and engineered for optimum all-weather performance with natural lighting effects, deliver professional results.

POWERED BY DESIGN PRO LED TECHNOLOGY

Enhance The Night - www.landlight.ca