

LED TIKI

A warm, soft center glow adds just the right hint of detail to this center mount LED path and spread.

15801 TZT - Textured Tannery Bronze™
(Marine grade powder coat)

Cast Aluminum

3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver

3000K (-200/+125) / 80s CRI

4 W, 5.8 VA
Multiply fixture VA by the number of fixtures used to determine size of transformer

9V-15V AC/DC with no loss in output due to constant current technology

Tested to an L-70 of 40,000 hours

3000K = 140 Lm
3000K = 35 Lm/W

24" of useable #18-2, SPT-1W leads.
Cable connector supplied

8" In-ground stake

15601 - Surface Mounting Flange
15607 - Surface Mounting Bracket

NA

Subjected to Highly Accelerated Life Testing - 3rd party reliability testing. Not for use with electronic transformers

Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8'

Footcandles 6.22 3.8 2.8 1.41 0.76 0.43 0.3 0.19 0.12

WT801

LandLight
Enhance The Night



Guaranteed not to burn out for 15 years (10 commercially)

POWERED BY
DESIGN PRO LED
TECHNOLOGY

WITH
Radiax
OPTICS

Professional-grade LED lighting and system components, designed and engineered for optimum all-weather performance with natural lighting effects, deliver professional results.

Enhance The Night - www.landlight.ca