

LED SIDE MOUNT

LED technology is combined with a side mount design for more directional lighting, without glare. Coordinates with matching LED deck light 15765 on page 24.

15815 AZT - Textured Architectural Bronze (Marine grade powder coat)
 15815 BE - Beach (Marine grade powder coat)
 15815 BKT - Textured Black (Marine grade powder coat)

Cast Aluminum

3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver

3000K (-200/+125) / 80s CRI

4 W, 5.8 VA
 Multiply fixture VA by the number of fixtures used to determine size of transformer

9V-15V AC/DC with no loss in output due to constant current technology

Tested to an L-70 of 40,000 hours

3000K = 140 Lm/W (High) 3000K = 80 Lm/W (Low)
 3000K = 35 Lm/W (High) 3000K = 20 Lm/W (Low)

53" of usable #18-2, SPT-1-W leads. Cable connector supplied

8" in-ground stake

15601 - Surface Mounting Flange
 15607 - Surface Mounting Bracket

15695 CLR - Sprinkler Shield

15315 - on page 95

Subjected to Highly Accelerated Life Testing - 3rd party reliability testing
 Not for use with electronic transformers

Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'
Footcandles	31.5	17.2	6.7	2.5	1.2	0.5	-	-	-

Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'
Footcandles	21.3	12	4.1	1.7	0.7	0.2	-	-	-

Footcandles	21.3	12	4.1	1.7	0.7	0.2	-	-	-
-------------	------	----	-----	-----	-----	-----	---	---	---

High/Low
 SETTING



WT815

Guaranteed not to burn out for 15 years (10 commercially)



Professional-grade LED lighting and system components, designed and engineered for optimum all-weather performance with natural lighting effects, deliver professional results.



Enhance The Night - www.landlight.ca