

LED LLENTA

A simple yet clean design that blends the newest LED technology with tough as nails construction. Coordinates with 15820.

15821 AZT - Textured Architectural Bronze (Marine grade powder coat)
 15821 BBR - Bronzed Brass
 15821 CO - Unfinished Copper

Cast Aluminum, Cast Brass, Copper (with Natural Brass Accents)
 (Copper and brass will naturally patina over time)

3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver

3000K (-200/+125) / 80s CRI

4 W, 5.8 VA
 Multiply fixture VA by the number of fixtures used to determine size of transformer

9V-15V AC/DC with no loss in output due to constant current technology

Tested to an L-70 of 40,000 hours

3000K = 187 Lm
 3000K = 47 Lm/W

30" of usable #18-2, SPT-1-W leads. Cable connector supplied

8" In-ground stake

15601 - Surface Mounting Flange
 15607 - Surface Mounting Bracket

Subjected to Highly Accelerated Life Testing - 3rd party reliability testing
 Not for use with electronic transformers

Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8'

Footcandles 20.70 6.60 1.00 0.28 0.10 0.06 0.01 -- --



WT821

Guaranteed not to burn out for 15 years (10 commercially)



Professional-grade LED lighting and system components, designed and engineered for optimum all-weather performance with natural lighting effects, deliver professional results.



Enhance The Night - www.landlight.ca