

# LED BROAD ROOF

A sculpted spindle center is capped by a broad, shallow roof that diffuses and spreads LED light.

15833 AZT - Textured Architectural Bronze (Marine grade powder coat)

Cast Aluminum

3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver

3000K (-200/+125) / 80s CRI

4 W, 5.8 VA  
Multiply fixture VA by the number of fixtures used to determine size of transformer

9V-15V AC/DC with no loss in output due to constant current technology

Tested to an L-70 of 40,000 hours

3000K = 140 Lm  
3000K = 35 Lm/W

30" of usable #18-2, SPT-1-W leads. Cable connector supplied

8" in-ground stake

15601 - Surface Mounting Flange  
15607 - Surface Mounting Bracket

Subjected to Highly Accelerated Life Testing - 3rd party reliability testing  
Not for use with electronic transformers

Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8'

Footcandles 13.5 3.7 0.8 0.3 0.2 0.1 - - -



**WT833**

**Guaranteed not to burn out for 15 years (10 commercially)**

POWERED BY  
DESIGN PRO LED  
TECHNOLOGY

WITH  
**Radiax**  
OPTICS

**LandLight**  
Enhance The Night

**Professional-grade LED lighting and system components, designed and engineered for optimum all-weather performance with natural lighting effects, deliver professional results.**

**Enhance The Night - [www.landlight.ca](http://www.landlight.ca)**