		4390	ż.	and the second
	LED WALL WA	SH	and the second	
illuminat	ign Pro LED Wall Wash creates a low, even light spread that tes shrubs, plants and textured wall surfaces and silhouettes special Fully adjustable knuckle.	22.24	gh/Low Itting	
15861 E	AZT - Textured Architectural Bronze™ (Marine grade powder coat) 3BR - Bronzed Brass 3KT - Textured Black (Marine grade powder coat)		BBR	CAST BRASS
Cast Aluminum, Cast Brass				
3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver				
Vertical = 108° Horizontal = 111°				
3000K (-	-200/+125) / 80s CRI	No. of Contraction	Î	
	V, 5.8 VA Low 2.5 W, 4 VA fixture VA by the number of fixtures used to determine size of mer		Adjustable	
9V-15V	AC/DC with no loss in output due to constant current technology			
Tested to	o an L-70 of 40,000 hours		San Manager and	* **** *******************************
3000K = 140 Lm (High) 80 Lm (Low) 3000K = 35 Lm/W (High) 20 Lm/W (Low)				Guaranteed not to burn out for 15 years (10
64" of us	sable #18-2, SPT-1-W leads			commercially)
8" In-gro	bund stake		AZT	POWERED BY
15607 -	Surface mounting flange Surface mounting bracket 90° Elbow			DESIGN PRO LED TECHNOLOGY WITH
Distance from Wall	0' 6" 1' 2' 3' 4' 5'6' (Horizontal Distance from Center)		BKT	Radiax [™]
2"	16.512.3 8.0 2.6 0.9 0.2 .00 .00	The second		
4"	4.4 4.3 3.8 2.7 1.7 1.0 0.7 0.4 WT857			



Professional-grade LED lighting and system components, designed and engineered for optimum all-weather performance with natural lighting effects, deliver professional results.

Enhance The Night - www.landlight.ca