

LED CAST HAMMERED ROOF

Pierced shade sheds decorative patterned LED light over shrubs, gardens, or walkways. Coordinates with matching LED deck light 15763 on page 23.

15871 BBR - Bronzed Brass (Marine grade powder coat)
 15871 TZT - Textured Tannery Bronze™ (Marine grade powder coat)

Cast Aluminum, Cast Brass

3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver

3000K (-200/+125) / 80s CRI

4 W, 5.8 VA

Multiply fixture VA by the number of fixtures used to determine size of transformer

9V-15V AC/DC with no loss in output due to constant current technology

Tested to an L-70 of 40,000 hours

3000K = 187 Lm
 3000K = 47 Lm/W

30" of useable #18-2, SPT-1W leads. Cable connector supplied

8" In-ground stake

15601 - Surface Mounting Flange
 15607 - Surface Mounting Bracket

15471 - on page 81

Subjected to Highly Accelerated Life Testing - 3rd party reliability testing
 Not for use with electronic transformers

Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8'

Footcandles 10.9 5.8 2.3 1.0 0.43 0.25 0.13 0.06 0.01

WT871



Guaranteed not to burn out for 15 years (10 commercially)



Professional-grade LED lighting and system components, designed and engineered for optimum all-weather performance with natural lighting effects, deliver professional results.



Enhance The Night - www.landlight.ca